

REPEATER THAT REPORTS DETECTED NEIGHBORS

TECHNICAL FIELD

[0001] The disclosure relates to wireless communication and, more particularly, wireless communication systems that make use of repeaters.

Related Applications

[0002] This application claims priority to U.S. Provisional No. 60/559,545, filed on April 5, 2004.

BACKGROUND

[0003] In a wireless communication system, base stations typically provide network access to subscriber units. A subscriber unit generally refers to a mobile wireless device used by an end user, such as a mobile radiotelephone. Base stations are generally stationary equipment that wirelessly communicate with the subscriber units to provide the subscriber units with access to a wired telecommunication network. For example, the base stations may provide an interface between the subscriber units and a public switched telephone network (PSTN) such that telephone calls can be routed to and from the subscriber units. Alternatively or additionally, the base stations may be coupled to a packet-based network for transmission of packet-based voice information or packet-based data.

[0004] In some areas, repeaters are installed in a wireless communication system in order to extend network coverage associated with one or more of the base stations. A repeater generally refers to a network device that receives signals from a base station, and retransmits substantially the same signals to the subscriber units. In some cases, repeaters may be wired to the base station, e.g., via a fiber optic link, and in other cases, repeaters are completely wireless. Wireless repeaters typically receive a signal, amplify the signal, and then retransmit the amplified signal to the subscriber units.

[0005] Repeaters are commonly considered a cost-effective mechanism for extending or improving network coverage. In particular, the use of repeaters can effectively broaden the geographical coverage area associated with a given base station. Moreover, the cost of implementing a repeater can be significantly less than the cost of adding an additional

base station. Implementing repeaters in a wireless communication system, however, raises a number of challenges and potential difficulties.

SUMMARY

[0006] In one embodiment, this disclosure is directed to a method comprising receiving information in a wireless communication system, the information being indicative of signals of a set of base stations that a repeater can detect in the wireless communication system, and updating a neighbor list based on the received information.

[0007] In another embodiment, this disclosure is directed to a method executed in a repeater of a wireless communication system. The method comprises identifying signals associated with a set of base stations that the repeater can detect, and sending information indicative of the set of base stations to a specific base station that gets repeated by the repeater.

[0008] Various embodiments are directed to a repeater, a base station control device, methods implemented in the repeater or the base station control device, and wireless communication systems that include the repeater, one or more base stations and a base station control device. In some cases, the techniques described herein may be implemented as software within a repeater or base station control device. Accordingly, this disclosure also contemplates computer readable media comprising computer readable instructions that, when executed, perform one or more of the techniques described herein.

[0009] The details of one or more embodiments of this disclosure are set forth in the accompanying drawings and the description below. Other features, objects, and advantages of this disclosure will be apparent from the description and drawings, and from the claims.

BRIEF DESCRIPTION OF DRAWINGS

[0010] FIG. 1 is a system diagram of a wireless communication system capable of implementing one or more aspects of this disclosure.

[0011] FIG. 2 is a block diagram of a repeater according to an exemplary embodiment of this disclosure.

[0012] FIG. 3 is a block diagram of a portion of the wireless communication system shown in FIG. 1, illustrating an exemplary base station control device in more detail.

[0013] FIG. 4 is a flow diagram illustrating exemplary operation of a repeater according to an embodiment of this disclosure.

[0014] FIG. 5 is a flow diagram illustrating exemplary operation of a base station control device according to an embodiment of this disclosure.

DETAILED DESCRIPTION

[0015] In general, this disclosure is directed to a repeater implemented in a wireless communication system, and a base station control device that uses information identified by the repeater. The repeater includes a control unit capable of detecting signals sent from various base stations in the wireless communication system. In accordance with this disclosure, the repeater identifies a set of base stations that it can detect, and then sends information indicative of the set of base stations that the repeater can detect to a specific base station associated with the repeater. The specific base station associated with the repeater generally refers to a base station that sends signals that get repeated by the repeater, i.e., the a base station that gets repeated by the repeater. The base station sends the information received from the repeater to a base station control device, which makes use of the information as described below.

[0016] By way of example, in a code division multiple access (CDMA) system, the repeater can search for pilot symbols in every possible pseudo-random noise (PN) offset defined by the CDMA system. If pilot symbols are detected at a particular PN offset, the repeater can send information indicating the detection of pilot symbols in that PN offset. In this manner, the repeater can be used to help assess network topology.

[0017] When the base station control device receives information from the repeater indicative of the set of base stations that the repeater can detect, e.g. via the base station associated with the repeater, the base station control device can use the information to update its neighbor list. That base station control device can then cause base stations to send updated neighbor lists to one or more subscriber units of the wireless communication system in order to facilitate handoffs. As an additional option, the repeater could also provide additional information such as energy levels, e.g., E_c/I_o levels (the energy per chip of the pilot symbols), signal to noise ratios, received signal

strength, or the specific pilots that were observed. In other words, the repeater could not only report which base stations that it can detect, but may also report the specific characteristics of the base station signals that it can detect. The base station, in turn can provide this information to a base station control device in order to facilitate improved network control. The base station control device, for example, may use such information to improve "OA & M" (operation, administration and maintenance) of the system.

[0018] A handoff refers to a process in which a subscriber unit changes from receiving service from one base station to another base station. In order to facilitate handoffs, the subscriber unit receives a neighbor list from its current base station, and searches for signals of the base stations in the neighbor list. If a signal of a neighboring base station is detected, the subscriber unit will send an indication of detection of the neighboring base station back to its current serving base station. A base station control device which controls the base stations will cause the subscriber unit to "handoff" to the neighboring base station if the signal of the neighboring base station becomes preferred, e.g., in terms of signal strength, or the like. In that case, forward link information will be sent from both base stations for a period of time, until the handoff is complete. Following a handoff, the subscriber unit would subsequently receive from the neighboring base station, a new neighbor list, which can be searched in order to possibly facilitate another handoff. In this manner, handoffs allow a subscriber unit to change base stations, even during cellular voice or data telephone calls.

[0019] The implementation of repeaters can significantly affect neighbor lists because repeaters generally extend the geographical network coverage associated with a given base station. Without repeaters, a neighbor list of a given base station typically includes only those base stations that are within a certain geographical radius of the given base station. However, when a repeater is used, the neighbor list of the base station associated with the repeater should account for the fact that the repeater is extending the network coverage of the base station. In that case, the neighbor list should include additional base stations that are relatively close to the repeater, even if those additional base stations are relatively far from the base station associated with the repeater. In some cases, repeaters are implemented to extend along highways, thereby significantly extending the geographical distance of a base station to the subscriber units it services along narrow geographical bands, e.g., corresponding to the highways.

[0020] Conventionally, following implementation of a repeater, a network technician manually surveys the network and updates the neighbor lists of the base station control device based on the presence of the repeater. Such manual updates to neighbor lists, however, are a costly use of human resources. Moreover, if network settings change in the future, the neighbor lists may become inaccurate. For this reason, in accordance with this disclosure, the repeater includes circuitry that allows the repeater to identify signals from various surrounding base stations. Accordingly, the repeater identifies signals of a set of base stations that it can detect, and then sends information indicative of the set of base stations that the repeater can detect to the specific base station associated with the repeater in order to allow for automatic updates of the neighbor list in the base station control device.

[0021] FIG. 1 is a system diagram of a wireless communication system 10, including one or more base stations 12A-12C (collectively base stations 12), one or more repeaters 14, and one or more subscriber units 16. Base stations 12 are coupled to a base station control device 18 which generally controls base stations 12. Base station control device 18 may be coupled to a mobile switching center 4. Mobile switching center 4, in turn, may be coupled to a public switching telephone network (PSTN) 8.

[0022] Repeater 14 is typically associated with a specific one of base stations 12, in this case, base station 12A. In other words, repeater 14 repeats signals sent from base station 12A. In particular, repeater 14 receives signals 15A from base station 12A, and repeats signals 15A (the repeated signal being labeled 15A') in order to extend network coverage of base station 12A. However, it may also be possible for a repeater 14 to repeat the signals of two or more base stations.

[0023] Base stations 12 are generally stationary equipment that wirelessly communicate with subscriber unit 16 in order to provide network access to subscriber unit 16. Base stations 12 can provide an interface between subscriber unit 14 and PSTN 8 such that telephone calls can be routed to and from subscriber unit 16. Again, base station control device 18 controls base stations 12 and interfaces with PSTN 8 via mobile switching center 4. Alternatively or additionally, base stations 12 may be coupled either directly or indirectly to a packet-based network for transmission of packet-based voice information or packet-based data. Base stations 12 are sometimes referred to as base transceiver systems (BTS).

[0024] Subscriber unit 16 generally refers to a wireless device used by an end user. Although a single subscriber unit 16 is illustrated, system 10 typically includes a plurality of such units. Subscriber unit 16 typically comprises a mobile radiotelephone. However, subscriber unit 16 may also be implemented in any of a wide variety of other portable computing devices such as a desktop or portable computer, a personal digital assistant (PDA), an interactive television, a wireless data terminal, a wireless data collection device, or any other wireless device.

[0025] Repeater 14 comprises a network device that receives signals 15A from a base station 12A and retransmits substantially the same signal 15A' to subscriber unit 16. Alternatively or additionally, repeater 14 may receive signals 15A' from subscriber unit 16 and retransmit substantially the same signal 15A to base station 12A. Although illustrated as a completely wireless device, in other examples, repeater 14 may be wired to base station 12A, e.g., via a fiber optic link, copper wiring or the like. In that case, however, the wired repeater would only hear the attached base station on the donor side, i.e., base station 12A.

[0026] In accordance with this disclosure, repeater 14 identifies signals 17B-17C (collectively signals 17) of a set of base stations 12B-12C that it can detect, and then sends information indicative of the set of base stations 12B-12C that repeater 14 can detect to base station 12A that is repeated by repeater 14. Base station 12A, in turn forwards this information to base station control device 18.

[0027] For example, if system 10 is a CDMA system, repeater 14 can search for pilot symbols in every possible pseudo-random noise (PN) offset defined by the CDMA system. If pilot symbols are detected at a particular PN offset, repeater 14 sends information to base station 12A indicating the detection of pilot symbols in that PN offset. In this manner, repeater 14 can be used to identify the presence of neighboring base stations or otherwise assess network topology of system 10. The signals 17 detected by repeater 14 may come directly from base stations 12B-12C, as illustrated in FIG. 1, or alternatively, one or more of signals 17 may come from another repeater, e.g., associated with one or more of base stations 12B-12C.

[0028] When base station control device 18 receives the information indicative of signals 17 of the set of base stations 12B-12C that repeater 14 can detect, e.g., via base station 12A, base station control device 18 uses the information to update its neighbor list. Base station control device 18 can then cause base station 12A to send the updated

neighbor list to subscriber unit 16 and other subscriber units of wireless communication system 10 in order to facilitate handoffs. Also, base station control device 18 may use this information for other purposes such as OA & M purposes. For example, the specific details about the strength and nature of the signals may be useful to base station control device 18 for OA & M purposes.

[0029] By using repeater 14 to detect signals 17 of base stations 12B-12C, and then report the signals it detects, system 10 can be significantly improved. For example, the need for a technician to manually survey the topology of network 10, following the implementation of repeater 14 may be reduced or eliminated. Moreover, because repeater 14 detects and reports the actual signals 17 that it detects, the neighbor list may be more accurate than a list generated by a technician's survey. Also, in accordance with this disclosure, the updated neighbor list should account for any network changes that occur, even if they occur after repeater 14 is deployed. For example, if base station 12C temporality malfunctions, the neighbor list of base station control device 18 can be updated automatically when repeater 14 no longer detects signal 17C. Also, if additional base stations or repeaters are later deployed, the neighbor list of base station control device 18 can be updated automatically when repeater 14 detects new signals associated with the newly deployed base stations or repeaters. In this manner, using repeater 14 to detect signals 17 and then report the signals it detects to base station 12A can improve performance of wireless communication system 10.

[0030] FIG. 2 is a block diagram of an exemplary repeater 14. In FIG. 2, the illustrated components include specific components that can be used in accordance with the teaching of this disclosure. However, other components may also exist, e.g., in order to control other repeater functions. In this example, repeater 14 includes a first antenna 22 (sometimes referred to as a "donor" antenna) to receive signals from base station 12A, and a first amplifier 24 to amplify the signals received at first antenna 22. In addition, repeater 14 includes a second antenna 26 (sometimes referred to as a "server" antenna) to transmit, i.e., to repeat, the signals received by first antenna 22 and amplified by amplifier 24. Also, repeater 14 may include a second amplifier 28 to amplify signals received at second antenna, e.g., from subscriber unit 16. In that case, first antenna 22 transmits, i.e., repeats, the signals received at second antenna 26.

[0031] In accordance with this disclosure, repeater 14 further includes a control unit 25. For example, control unit 25 may comprise a digital signal processor (DSP) executing

software modules, a programmable microprocessor, or discrete hardware components. Also, control unit 24 may be implemented in any combination of hardware, software, firmware, one or more programmable microprocessors, digital signal processors, or the like. In one example, control unit 24 comprises a DSP or chip-set similar to those typically implemented in subscriber units. In that case, the DSP can be programmed to perform the signal processing techniques of repeater 14 as described herein. The various components of repeater 14 are illustrated for purposes of explanation, but may be integrated with other components, e.g., within hardware or software. If the techniques described herein are implemented in software, a memory or other computer-readable medium (not shown) may be coupled to control unit 25 in order to store the software instructions loaded into control unit 25 for execution. If the techniques are executed in digital, repeater 14 would typically include an analog-to-digital converter (not shown) to convert received signals to digital values, which can be processed by control unit 25, e.g., in the form of a DSP.

[0032] In any case, control unit 25 examines incoming signals received at antenna 22 in order to identify signals 17 (FIG. 1) received from various neighboring base stations 12B-12C. In particular, control unit 25 detects signals 17 and then generates information indicative of detected signals 17 associated with neighboring base stations 12B-12C. For example, control unit 25 may scan received signals for the presence of pilot symbols at different PN offsets, e.g., which correspond to signals 17. Alternatively, control unit 25 may identify network identification (ID) codes from received signals, e.g., obtained from overhead channels of respective signals 17. In any case, control unit 25 then causes repeater 14 to transmit the generated information indicative of detected signals 17 associated with neighboring base stations 12B-12C to base station 12A. Base station 12A, then forwards this information to base station control device 18 so that its neighbor list can be updated. Again, signals 17 associated with neighboring base stations 12B-12C may come directly from base stations 12B-12C, as illustrated in FIG. 1, or alternatively, one or more of signals 17 may come from another repeater, e.g., associated with one or more of base stations 12B-12C.

[0033] In one example, where system 10 comprises a CDMA system, control unit 25 examines received signals 17 and searches for pilot symbols in possible pseudo-random noise (PN) offsets defined by the CDMA system. If pilot symbols are detected at a particular PN offset, control unit 25 identifies the presence of pilot symbols, and causes

repeater 14 to send information to base station 12A indicating the detection of pilot symbols in that particular PN offset. In this manner, control unit 25 of repeater 14 can be used to help identify the presence of base stations 12B-12C, or otherwise assess network topology of system 10, e.g., for the purpose of updating the neighbor list of base station control device 18.

[0034] FIG. 3 is a block diagram of a portion of system 10, illustrating an exemplary base station control device 18 in more detail. In FIG. 3, the illustrated components of base station control device 18 are specifically those components used in receiving information and updating neighbor lists in accordance with this disclosure. Numerous other components exist in base station control device 18 for other functions, such as for O A & M purposes. For simplicity, however, the additional components are not illustrated.

[0035] As shown in FIG. 3, base station control device 18 includes a controller 36, and a neighbor list database 38. Neighbor list database 38 stores a list of base stations that are considered neighbors to base station 12A in the context of handoffs. Controller 36 periodically fetches the neighbor list from database 38 and causes base station 12A to broadcast the neighbor list to various subscriber units currently registered through base station 12A. The subscriber units, then, use the neighbor list sent from base station 12A to define searches for signals of the neighboring base stations. If necessary, the subscriber units 16 can then perform handoffs to the neighboring base stations identified in the neighbor list.

[0036] In accordance with this disclosure, base station 12A receives from repeater 14, information indicative of signals 17 from a set of base stations 12B-12C that repeater 14 can detect (see FIG. 1). The information sent from repeater 14 is then forwarded from base station 12A to base station control device 18. Controller 36 of base station control device 18 uses the information to update its neighbor list maintained in neighbor list database 38.

[0037] By updating the neighbor list of base station control device 18 maintained in neighbor list database 38 based on information identified by repeater 14, the performance of system 10 can be improved. In particular, the information indicative of signals 17 received from a set of base stations 12B-12C that repeater 14 can detect, allows base station control device 18 to update its neighbor list maintained in neighbor list database 38 in order to account for the fact that base stations 12B-12C are within the

coverage area of base station 12A by virtue of the presence of repeater 14. Then, when base station 12A is caused to broadcast its neighbor list, other subscriber units will know to search for base stations 12B-12C in order to facilitate handoffs. Moreover, if network topology changes, e.g., by the addition of other base stations or repeaters, or the elimination or malfunction of base stations or repeaters, repeater 14 will send new information to base station 12A identifying the absence or addition of base station signals in system 10, which allows the neighbor list of base station control device 18 to be adjusted accordingly. In this manner, operation of the various devices of system 10 can be improved.

[0038] FIG. 4 is a flow diagram illustrating exemplary operation of repeater 14 according to an embodiment of this disclosure. As shown in FIG. 4, control unit 25 of repeater 14 detects pilot symbols, e.g., within signals 17 sent from base stations 12B-12C (41). Then, control unit 25 identifies offsets associated with the various detected pilot symbols (42). For example, if system 10 comprises a CDMA system, control unit may identify PN offsets of the various pilot symbols, relative to system time. In that case, the PN offsets define the proper search times that can be subsequently used by various subscriber units in searching for the pilot symbols of base stations 12B-12C.

[0039] Alternatively, control unit 25 may identify ID codes associated with base stations 12B-12C. In any case, control unit 25 then causes repeater 14 to send information indicative of the identified offsets to base station 12A (43). Accordingly, base station 12A can forward the information to base station control device 18 so that the neighbor list can be updated. The process illustrated in FIG. 4 can eliminate or reduce the need for a technician to manually update the neighbor lists of base station control device 18, following implementation of repeater 14. Moreover, the process of FIG. 4 can allow for automatic and dynamic adjustments to the neighbor list, e.g., in response to the addition, elimination or malfunction of base stations or repeaters within system 10.

[0040] FIG. 5 is a flow diagram illustrating exemplary operation of base station control device 18 according to an embodiment of this disclosure. As shown in FIG. 5, base station control device 18 receives information identified by repeater 14 indicative of signals 17 of a set of base stations 12B-12C that repeater 14 can detect (51). Controller 36 updates a neighbor list stored in neighbor list data base 38 based on the received information (52).

[0041] Once the neighbor list has been updated (52), controller 36 causes base station 12A to send the updated neighbor list to various subscriber units (53). Once the updated neighbor list is sent to various subscriber units, those subscriber units can use the updated neighbor list to facilitate searches and handoffs. Importantly, because the neighbor list is updated based on information identified by repeater 14 indicative of signals 17 of set of base stations 12B-12C that repeater 14 can detect, the subscriber units will search for signals 17, and possibly perform handoffs to one of base stations 12B-12C.

[0042] Various embodiments of the have been described. In particular, a wireless communication system has been described in which a repeater in the system identifies signals of a set of base stations that the repeater can detect. In accordance with this disclosure, the signals of a set of base stations that the repeater can detect may come directly from the different base stations, e.g., as illustrated in FIG. 1, or may alternatively come from other repeaters associated with the various base stations.

[0043] After identifying signals of a set of base stations that the repeater can detect, the repeater then reports information indicative of the signals to a specific base station associated with the repeater. The base station then forwards this information to a base station control device, which updates its neighbor list based on the information it receives from the repeater. Updated neighbor lists can then be sent to subscriber units. The subscriber units can use the updated neighbor list to search for neighboring base stations for the purpose of facilitating handoffs.

[0044] The techniques described herein may be implemented in a subscriber unit or base station in hardware, software, firmware, or the like. Example hardware implementations include implementations within a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA), a programmable logic device, specifically designed hardware components, or any combination thereof. In addition, one or more of the techniques described herein may be partially or wholly executed in software. In that case, a computer readable medium may store or otherwise comprise computer readable instructions, i.e., program code, that can be executed by a processor or DSP of a subscriber unit or base station to carry out one of more of the techniques described above.

[0045] For example, the computer readable medium may comprise random access memory (RAM), read-only memory (ROM), non-volatile random access memory

(NVRAM), electrically erasable programmable read-only memory (EEPROM), flash memory, or the like. The computer readable medium can be coupled to control unit 24 of subscriber unit 16, or coupled to controller 36 of base station control device 18. In those cases, control unit 24 or controller 36 may comprise a processor or DSP that executes various software modules stored in the computer readable medium.

[0046] Numerous other modifications may be made without departing from the spirit and scope of this disclosure. For example, although many of the techniques have been described in the context of CDMA systems, the techniques may also be applicable to other systems such as time division multiple access (TDMA) systems, frequency division multiple access (FDMA) systems, systems such as the global system for mobile communication (GSM) that use combinations of TDMA and FDMA techniques, or the like. Also, neighbor lists have been described as being stored in base station control device 18, they could alternatively be stored and updated in other devices of a wireless communication system, such as within base stations 12 or within mobile switching center 4, or a similar device. Accordingly, these and other embodiments are within the scope of the following claims.

DATE 7-24-07

APPLICATION NUMBER 101534416

DOC CODE CLM

DOC DATE _____

DELIVER THE ATTACHED FILE/DOCUMENT TO THE TC
SCANNING CENTER

CONTRACTOR: THE ATTACHED FILE/DOCUMENT MUST BE
INDEXED AND SCANNED INTO IFW WITHIN 8 WORK HOURS;
UPLOADING OF THE SCANNED IMAGES SHOULD OCCUR NO
LATER THAN 16 WORK HOURS
FOLLOWING RECEIPT OF THIS REQUEST

AFTER SCANNING, ORIGINAL DOCUMENTS SHOULD BE BOXED IN
ACCORDANCE WITH INSTRUCTIONS